

Tungsten Disulfide (WS₂) Aerosol Spray (Product No: MK-WS2-SP)

Tungsten Disulfide (WS₂) Aerosol Spray offers convenient way to apply thin film of Tungsten Disulfide (WS₂) coating on any surface as well as in hard to reach places. Tungsten Disulfide (WS₂) Spray provides extreme lubricity, dry lubricant film on a substrate.

- Bonds well with substrates and form a coating film
- WS₂ is chemically inert
- High Temperature lubrication (temperature range of -50° C to + 600° C)
- Very high load bearing properties
- Contains no fluorocarbons or lead
- Not harmful to Ozone

Suggested applications:

- Automotive parts, car engine, piston & piston cylinders
- Bearings
- Carbon brush solid lubricant
- Cams & cam followers
- Power transmission components
- Machinery components, precision gears
- Plastic molds & extrusion dies for release
- Aerospace & defense components
- Marine parts
- Sliding & rotating components
- Valve components & actuators
- Rollers, spindles, shafts & seals
- Robotics
- Sporting goods
- Cutting tools, blades, slitters & knives, punches & dies
- Bullet & ammunition parts

Packing: 13 Oz/369 grams per can (Read MSDS before use)

Product Numbers:

MK-WS2-SP/01: 1 can

MK-WS2-SP/02: Box of 12 cans

MK-WS2-SP/03: Carton of 48 cans



www.lowerfriction.com

M K Impex Corp.

6382 Lisgar Drive

Mississauga, Ontario L5N 6X1

Canada

Phone: 416-509-4462; Fax: 905-824-1259

E-mail: sales@lowerfriction.com